

ASO

ASO, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz

Article 103.527



[To the product item](#)

Technical data

| | | |
|-----------------------------|---------------|------------|
| Blower type | Radial blower | |
| Phases | 3x | |
| Voltage at 50 Hz | 230/400 V | |
| Voltage at 60 Hz | 265/460 V | |
| Frequency | 50/60 Hz | |
| Blower power at 50 Hz | 550 W | |
| Blower power at 60 Hz | 660 W | |
| Airflow (20 °C) at 50 Hz | 13500 l/min | 476.74 cfm |
| Airflow (20 °C) at 60 Hz | 15900 l/min | 561.5 cfm |
| Static pressure at 50 Hz | 1600 Pa | 0.23 psi |
| Static pressure at 60 Hz | 2400 Pa | 0.34 psi |
| Max. air inlet temperature | 200 °C | 392 °F |
| Max. ambient temperature | 60 °C | 140 °F |
| Noise emission level | 70 dB (A) | |
| Air inlet (outer diameter) | 134 mm | 5.27 in |
| Air outlet (outer diameter) | 90 mm | 3.54 in |
| Length | 366 mm | 14.4 in |
| Width | 361 mm | 14.21 in |
| Height | 366 mm | 14.4 in |
| Weight | 15 kg | 33.06 lb |
| Power cable length | 0 m | 0 ft |
| Plug | without plug | |



ASO

ASO, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz

Article 103.527

Technical data

| | |
|------------------------------|---------------|
| Approvals | CE; EAC; UKCA |
| Protection class (IEC 60529) | IP54 |
| Protection class | I |