

# ROBUST

ROBUST, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz

Article 103.429



**To the product item**

## Technical data

Blower type	Side channel blower	
Phases	3x	
Voltage at 50 Hz	230/400 V	
Voltage at 60 Hz	265/460 V	
Frequency	50/60 Hz	
Blower power at 50 Hz	250 W	
Blower power at 60 Hz	300 W	
Airflow (20 °C) at 50 Hz	1200 l/min	42.37 cfm
Airflow (20 °C) at 60 Hz	1300 l/min	45.9 cfm
Static pressure at 50 Hz	8000 Pa	1.16 psi
Static pressure at 60 Hz	10500 Pa	1.52 psi
Max. air inlet temperature	60 °C	140 °F
Max. ambient temperature	60 °C	140 °F
Noise emission level	62 dB (A)	
Air inlet (outer diameter)	38 mm	1.49 in
Air outlet (outer diameter)	38 mm	1.49 in
Length	257 mm	10.11 in
Width	227 mm	8.93 in
Height	221 mm	8.7 in
Weight	8 kg	17.63 lb
Power cable length	0 m	0 ft
Plug	without plug	



# ROBUST

ROBUST, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz

Article 103.429

## Technical data

Approvals	CE; UKCA
Protection class (IEC 60529)	IP54
Protection class	I