TWINNY S

TWINNY S, 230V/2900W, combi-wedge short, 144:1, EU plug
Article 119.024

To the product item

Technical data

Article	119.024	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2900 W	
Temperature	20–600 °C	68–1112 °F
Air volume adjustable	Yes	
Speed	0.8–4 m/min	2.62–13.12 ft/min
Welding Technology	Combi-wedge	
Combi-wedge version	Short	
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Steel roller sharp diagonal	
LQS	No	
Brushless blower motor	No	
Display	No	
Length	350 mm	13.77 in
Width	390 mm	15.35 in
Height	270 mm	10.62 in
Weight	6.9 kg	15.21 lb
Welding materials	CSPE; EPDM; FPO; HDPE; LDPE; LLDPE; PP; PVC; TPO	
Weldable material thicknesses	0.3–2 mm	11.81–78.74 mil
Plug	EU, 3 poles, 16A	

© Copyright Leister Technologies AG, 2025 | Subject to changes

TWINNY S

TWINNY S, 230V/2900W, combi-wedge short, 144:1, EU plug
Article 119.024

Technical data

Power cable length	3 m	9.84 ft
Approvals	CE; KC	
Protection class	II	
Country of origin	Switzerland	

Scope of delivery

126.448 Tool case

© Copyright Leister Technologies AG, 2025 | Subject to changes