

# MISTRAL 6 SYSTEM

MISTRAL 6 SYSTEM, 200V/3000W, ø50mm

Article 147.973



To the product item



## Technical data

|                             |               |                |
|-----------------------------|---------------|----------------|
| Phases                      | 1x            |                |
| Voltage                     | 200 V         |                |
| Current                     | 15 A          |                |
| Power                       | 3000 W        |                |
| Frequency                   | 50/60 Hz      |                |
| Air temperature control     | Closed loop   |                |
| Max. air outlet temperature | 650 °C        | 1202 °F        |
| Airflow (20°C)              | 100-350 l/min | 3.53-12.36 cfm |
| Max. air inlet temperature  | 60 °C         | 140 °F         |
| Max. ambient temperature    | 65 °C         | 149 °F         |
| Overheating protection      | Yes           |                |
| Static pressure             | 3500 Pa       | 0.5 psi        |
| Nozzle connection ø         | 50 mm / 2 in  |                |
| Noise emission level        | 65 dB (A)     |                |
| Display                     | Yes           |                |
| Interfaces                  | 0-10V; 4-20mA |                |
| Length                      | 322.5 mm      | 12.69 in       |
| Width                       | 90 mm         | 3.54 in        |
| Height                      | 91.2 mm       | 3.59 in        |
| Weight                      | 1.4 kg        | 3.08 lb        |
| Approvals                   | CE; S+; cURus |                |
| Protection class            | II            |                |