

# LHS 21L SYSTEM

LHS 21L SYSTEM, 230V/3.3kW

Article 140.461



**To the product item**

## Technical data

|                             |                       |          |
|-----------------------------|-----------------------|----------|
| Article                     | 140.461               |          |
| Phases                      | 1x                    |          |
| Voltage                     | 230 V                 |          |
| Current                     | 14 A                  |          |
| Power                       | 3300 W                |          |
| Max. air outlet temperature | 650 °C                | 1202 °F  |
| Min. airflow                | 260 l/min             | 9.18 cfm |
| Max. air inlet temperature  | 65 °C                 | 149 °F   |
| Max. ambient temperature    | 65 °C                 | 149 °F   |
| Air temperature control     | Closed loop           |          |
| Overheating protection      | Yes                   |          |
| Alarm output                | Normally open contact |          |
| Max. inlet pressure         | 100 kPa               | 14.5 psi |
| Nozzle connection ø         | 36.5 mm / 1.45 in     |          |
| Display                     | Yes                   |          |
| Interfaces                  | 0-10V; 4-20mA         |          |
| Length                      | 266 mm                | 10.47 in |
| Width                       | 67 mm                 | 2.63 in  |
| Height                      | 71 mm                 | 2.79 in  |
| Weight                      | 0.65 kg               | 1.43 lb  |
| Approvals                   | CE; EAC; S+           |          |
| Protection class            | II                    |          |