

GEOSTAR G7

GEOSTAR G7, 230V/2800W, copper test channel, UK plug

Article 156.310



To the product item



Technical data

Article	156.310	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2800 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-12 m/min	2.62-39.37 ft/min
Welding Technology	Hot wedge	
Hot wedge length	130 mm	5.11 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Copper	
Max. overlap	150 mm	5.9 in
Max. welding pressure	1500 N	337.21 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Steel roller sharp diagonal	
LQS	No	
Display	Yes	
Length	482 mm	18.97 in
Width	278 mm	10.94 in
Height	269 mm	10.59 in
Weight	18.1 kg	39.9 lb
Welding materials	FPO; HDPE; LDPE; LLDPE; PE; PP; TPO	
Weldable material thicknesses	1-3 mm	39.37-118.11 mil
Power cable length	3 m	9.84 ft
Plug	UK, 3 poles, 13A	



GEOSTAR G7

GEOSTAR G7, 230V/2800W, copper test channel, UK plug

Article 156.310

Technical data

Approvals	CB Certification; CE
Protection class	I
Country of origin	Switzerland

Scope of delivery

151.847 Cylinder brush, brass $\varnothing$ 15 mm; 173.145 Test certificate; 106.852 Allen wrench 3 mm; 100.530 Allen wrench 4 mm; 115.109 Allen wrench 5 mm; 153.777 Tool case