

TWINNY T7

TWINNY T7, 230V/3450W, combi-wedge long test channel, CEE 3/16

Article 164.198



To the product item



Technical data

Article	164.198	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3450 W	
Temperature	100-560 °C	212-1040 °F
Air volume adjustable	Yes	
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Combi-wedge	
Combi-wedge version	Long	
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Steel roller sharp diagonal	
Travel roller equipment	Field-Kit	
LQS	Yes	
Brushless blower motor	Yes	
Display	Yes	
Length	350 mm	13.77 in
Width	360 mm	14.17 in
Height	260 mm	10.23 in
Weight	10.5 kg	23.14 lb
Welding materials	CSPE; EPDM; FPO; HDPE; LDPE; LLDPE; PP; PVC; TPO	
Weldable material thicknesses	0.3-3 mm	11.81-118.11 mil



TWINNY T7

TWINNY T7, 230V/3450W, combi-wedge long test channel, CEE 3/16
Article 164.198

Technical data

Plug	CEE blue, 3 poles, 16A	
Power cable length	3 m	9.84 ft
Approvals	CE	
Protection class	I	
Country of origin	Switzerland	

Scope of delivery

151.847 Cylinder brush, brass ø 15 mm; 173.145 Test certificate; 162.760 Tool case