

# HT 330-S Universal Kit

HT 330-S, 230V/2000W, Universal Kit, UK plug

Article 128.782



[To the product item](#)



## Technical data

|                                |                  |             |
|--------------------------------|------------------|-------------|
| Article                        | 128.782          |             |
| Voltage                        | 230 V            |             |
| Frequency                      | 50/60 Hz         |             |
| Power                          | 2000 W           |             |
| Temperature                    | 80-600 °C        | 176-1112 °F |
| Temperature setting stepless   | Yes              |             |
| Air volume at level 1          | 250 l/min        | 8.82 cfm    |
| Air volume at level 2          | 550 l/min        | 19.42 cfm   |
| Stepless air volume adjustment | No               |             |
| Eco-Mode                       | No               |             |
| Display                        | No               |             |
| e-Drive                        | No               |             |
| Outdoor use                    | No               |             |
| Nozzle connection ø            | 35.5 mm / 1.4 in |             |
| Length                         | 359 mm           | 14.13 in    |
| Device diameter                | 90 mm            | 3.54 in     |
| Handle diameter                | 50 mm            | 1.96 in     |
| Weight                         | 0.65 kg          | 1.43 lb     |
| Power cable length             | 2 m              | 6.56 ft     |
| Plug                           | UK, 3 poles, 13A |             |
| Noise emission level           | 67 dB (A)        |             |
| Approvals                      | CE               |             |
| Protection class               | II               |             |
| Country of origin              | P.R. China       |             |

# HT 330-S Universal Kit

HT 330-S, 230V/2000W, Universal Kit, UK plug

Article 128.782

## Scope of delivery

---

119.341 Glass protection nozzle (ø 35.5) 50 x 5 mm; 119.343 Tubular nozzle (ø 35.5) ø 20 mm, 30 mm; 119.344 Spoon reflector (ø 35.5) 40 x 35 mm