

# miniwelder roof2

miniwelder roof2, 230V/800W, w/o test channel, EU plug  
Article 158.291



**To the product item**

## Technical data

Article	158.291	
Voltage	230 V	
Frequency	50/60 Hz	
Power	800 W	
Temperature	60-480 °C	140-896 °F
Speed	0.4-7.5 m/min	1.31-24.6 ft/min
Welding Technology	Hot wedge	
Hot wedge length	50 mm	1.96 in
Hot wedge width	40 mm	1.57 in
Hot wedge material	Hard ematalised aluminum	
Max. overlap	80 mm	3.14 in
Roll material	Silicone roller 50 shore A	
LQS	No	
Display	No	
Length	228 mm	8.97 in
Width	228 mm	8.97 in
Height	170 mm	6.69 in
Weight	3.7 kg	8.15 lb
Welding materials	PVC; TPO	
Weldable material thicknesses	0.3-1 mm	11.81-39.37 mil
Power cable length	3 m	9.84 ft
Plug	EU, 3 poles, 16A	
Approvals	CB Certification; CE	
Protection class	I	
Country of origin	P.R. China	

# miniwelder roof2

miniwelder roof2, 230V/800W, w/o test channel, EU plug

Article 158.291

## Scope of delivery

---

130.612 Wire brush, brass; 156.619 Allen wrench 3 mm