

COMET 700

COMET 700, 230V/2300W, copper 60x50mm test channel, CEE 3/16

Article 168.662



To the product item



Technical data

Article	168.662	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2300 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Hot wedge	
Hot wedge length	60 mm	2.36 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Copper	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Steel roller sharp diagonal	
Travel roller equipment	Field-Kit	
LQS	Yes	
Display	Yes	
Length	325 mm	12.79 in
Width	245 mm	9.64 in
Height	260 mm	10.23 in
Weight	9.4 kg	20.72 lb
Welding materials	FPO; HDPE; LDPE; LLDPE; PE; PP; TPO	
Weldable material thicknesses	0.5-3 mm	19.68-118.11 mil
Power cable length	3 m	9.84 ft
Plug	CEE blue, 3 poles, 16A	



COMET 700

COMET 700, 230V/2300W, copper 60x50mm test channel, CEE 3/16
Article 168.662

Technical data

Approvals	CE
Protection class	I
Country of origin	Switzerland

Scope of delivery

151.847 Cylinder brush, brass ø 15 mm; 173.145 Test certificate; 162.760 Tool case