

COMET 700

COMET 700, 230V/2300W, steel 90x50mm, CEE 3/16

Article 168.660



To the product item



Technical data

Article	168.660	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2300 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Hot wedge	
Hot wedge length	90 mm	3.54 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Roll material	Steel roller blunt diagonal	
Travel roller equipment	Field-Kit	
LQS	Yes	
Display	Yes	
Length	325 mm	12.79 in
Width	245 mm	9.64 in
Height	260 mm	10.23 in
Weight	9.4 kg	20.72 lb
Welding materials	CSPE; FPO; HDPE; LDPE; PE; PVC; TPO	
Weldable material thicknesses	0.5-3 mm	19.68-118.11 mil
Power cable length	3 m	9.84 ft
Plug	CEE blue, 3 poles, 16A	



COMET 700

COMET 700, 230V/2300W, steel 90x50mm, CEE 3/16

Article 168.660

Technical data

Approvals	CE
Protection class	I
Country of origin	Switzerland

Scope of delivery

151.847 Cylinder brush, brass $\varnothing$ 15 mm; 173.145 Test certificate; 162.760 Tool case