

COMET 700

COMET 700, 120V/1700W, steel 60x50mm, CEE 3/16

Article 168.653



To the product item



Technical data

Article	168.653	
Voltage	120 V	
Frequency	50/60 Hz	
Power	1700 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Hot wedge	
Hot wedge length	60 mm	2.36 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Roll material	Steel roller blunt diagonal	
Travel roller equipment	Indoor-Kit	
LQS	Yes	
Display	Yes	
Length	325 mm	12.79 in
Width	245 mm	9.64 in
Height	260 mm	10.23 in
Weight	9.4 kg	20.72 lb
Welding materials	CSPE; FPO; HDPE; LDPE; PE; PVC; TPO	
Weldable material thicknesses	0.5-3 mm	19.68-118.11 mil
Power cable length	3 m	9.84 ft
Plug	CEE yellow, 3 poles, 16A	



COMET 700

COMET 700, 120V/1700W, steel 60x50mm, CEE 3/16
Article 168.653

Technical data

Approvals	CE
Protection class	I
Country of origin	Switzerland

Scope of delivery

151.847 Cylinder brush, brass ø 15 mm; 173.145 Test certificate; 162.760 Tool case