

miniwelder geo2

miniwelder geo2, 120V/800W, copper wedge, US plug

Article 125.503



To the product item



Technical data

Article	125.503	
Voltage	120 V	
Frequency	50/60 Hz	
Power	800 W	
Temperature	60-480 °C	140-896 °F
Speed	0.4-7.5 m/min	1.31-24.6 ft/min
Welding Technology	Hot wedge	
Hot wedge length	50 mm	1.96 in
Hot wedge width	36 mm	1.41 in
Hot wedge material	Copper	
Max. overlap	100 mm	3.93 in
Weld seam width	2 x 12 mm / 2 x 0.47 in	
Roll material	Steel roller sharp straight	
LQS	No	
Display	No	
Length	228 mm	8.97 in
Width	228 mm	8.97 in
Height	170 mm	6.69 in
Weight	3.9 kg	8.59 lb
Welding materials	FPO; HDPE; LDPE; LLDPE; PE; PP	
Weldable material thicknesses	0.5-1.5 mm	19.68-59.05 mil
Power cable length	3 m	9.84 ft
Plug	US, 3 poles, 20A	

miniwelder geo2

miniwelder geo2, 120V/800W, copper wedge, US plug

Article 125.503

Technical data

Approvals	CB Certification; CE
Protection class	I
Country of origin	P.R. China

Scope of delivery

130.612 Wire brush, brass; 156.619 Allen wrench 3 mm