

# energy HT1600 D Overlap welding kit

energy HT1600 D, 230V/1600W, overlap kit, EU plug

Article 160.171



[To the product item](#)



## Technical data

Voltage	230 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40-620 °C	104.0-1148.0 °F
Temperature setting stepless	Yes	
Airflow (20°C)	120-240 l/min	4.23-8.47 cfm
Stepless air volume adjustment	Yes	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	360.0 mm	14.17 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	1.2 kg	2.64 lb
Power cable length	3.0 m	9.84 ft
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	CN	

## Scope of delivery

130.891 Wide slot nozzle (ø 31.5) 40 x 2 mm; 130.631 Wide slot nozzle (ø 31.5) 20 x 2 mm; 130.611 Pressure roller 40 mm, silicone; 125.810 Carbon brushes