

energy HT1600 D Overlap welding kit

energy HT1600 D, 230V/1600W, overlap kit, UK plug

Article 160.174



To the product item



Technical data

| | | |
|--------------------------------|-------------------|---------------|
| Article | 160.174 | |
| Voltage | 230 V | |
| Frequency | 50/60 Hz | |
| Power | 1600 W | |
| Temperature | 40-620 °C | 104-1148 °F |
| Temperature setting stepless | Yes | |
| Airflow (20°C) | 120-240 l/min | 4.23-8.47 cfm |
| Stepless air volume adjustment | Yes | |
| Static pressure | 2600 Pa | 0.37 psi |
| Eco-Mode | No | |
| Display | Yes | |
| e-Drive | Yes | |
| Outdoor use | Yes | |
| Nozzle connection ø | 31.5 mm / 1.25 in | |
| Length | 360 mm | 14.17 in |
| Device diameter | 101 mm | 3.97 in |
| Handle diameter | 59 mm | 2.32 in |
| Weight | 1.2 kg | 2.64 lb |
| Power cable length | 3 m | 9.84 ft |
| Plug | UK, 3 poles, 13A | |
| Noise emission level | 67 dB (A) | |
| Approvals | CE | |
| Protection class | II | |
| Country of origin | P.R. China | |

energy HT1600 D Overlap welding kit

energy HT1600 D, 230V/1600W, overlap kit, UK plug

Article 160.174

Scope of delivery

130.611 Pressure roller 40 mm, silicone; 125.810 Carbon brushes; 124.777 Wide slot nozzle (ø 31.5) 40 x 2 mm; 124.772 Wide slot nozzle (ø 31.5) 20 x 2 mm