

# energy HT1600 D Overlap welding kit

energy HT1600 D, 120V/1600W, overlap kit, US plug

Article 160.180



**To the product item**

## Technical data

Article	160.180	
Voltage	120 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40-620 °C 104-1148 °F	
Temperature setting stepless	Yes	
Airflow (20°C)	120-240 l/min	4.23-8.47 cfm
Stepless air volume adjustment	Yes	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection Ø	31.5 mm / 1.25 in	
Length	360 mm	14.17 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	1.2 kg	2.64 lb
Power cable length	3 m	9.84 ft
Plug	US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	P.R. China	

# **energy HT1600 D Overlap welding kit**

energy HT1600 D, 120V/1600W, overlap kit, US plug

Article 160.180

---

## **Scope of delivery**

130.611 Pressure roller 40 mm, silicone; 125.810 Carbon brushes; 124.777 Wide slot nozzle (ø 31.5) 40 x 2 mm; 124.772 Wide slot nozzle (ø 31.5) 20 x 2 mm