

energy HT1600 Overlap welding kit

energy HT1600, 230V/1600W, overlap kit, CN plug

Article 120.888



To the product item



Technical data

Article	120.888	
Voltage	230 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40-700 °C	104-1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	346 mm	13.62 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft
Plug	CN, 2 poles, 10A	
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	P.R. China	

energy HT1600 Overlap welding kit

energy HT1600, 230V/1600W, overlap kit, CN plug

Article 120.888

Scope of delivery

130.611 Pressure roller 40 mm, silicone; 124.777 Wide slot nozzle (ø 31.5) 40 x 2 mm; 124.772 Wide slot nozzle (ø 31.5) 20 x 2 mm