

energy HT1600 Plastic welding kit

energy HT1600, 120V/1600W, plastic kit, US plug

Article 120.886



To the product item



Technical data

Article	120.886	
Voltage	120 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40-700 °C	104-1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	346 mm	13.62 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft
Plug	US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	P.R. China	

energy HT1600 Plastic welding kit

energy HT1600, 120V/1600W, plastic kit, US plug

Article 120.886

Scope of delivery

146.740 Speed welding nozzle (ø 8.0) Profile D ø 4; 147.250 Tubular nozzle (ø 31.5) ø 5 mm, 37 mm; 125.810 Carbon brushes