

FUSION 3C

FUSION 3C, 230V/3200W, ø3/4mm, w/o shoe, CEE 3/16

Article 173.794



To the product item

Technical data

Article	173.794	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3200 W	
Welding rod	ø 3-4 mm / 0.12-0.16 in	
Material output ø 3 mm	2-2.5 kg/h	4.4-5.51 lb/h
Material output ø 4 mm	2.7-3.6 kg/h	5.95-7.93 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Weldable sheet/membrane thickness	15-25 mm	0.59-0.98 in
Air guide	Internal	
Screw heating	Air heated	
Air temperature control	Open loop	
LQS	No	
Display	No	
Brushless blower motor	No	
Brushless drive motor	No	
LED Working light	No	
Length	588 mm	23.14 in
Width	98 mm	3.85 in
Height	225 mm	8.85 in
Weight	6.9 kg	15.21 lb
Power cable length	5 m	16.4 ft
Plug	CEE blue, 3 poles, 16A	
Noise emission level	86 dB (A)	



FUSION 3C

FUSION 3C, 230V/3200W, \varnothing 3/4mm, w/o shoe, CEE 3/16

Article 173.794

Technical data

Approvals CB Certification; CE

Protection class II

Country of origin Switzerland

Scope of delivery

119.540 Tool case