

FUSION 2

FUSION 2, 230V/2800W, CH plug
Article 176.837



To the product item

Technical data

| | | |
|-----------------------------------|-----------------------|----------------|
| Article | 176.837 | |
| Voltage | 230 V | |
| Frequency | 50/60 Hz | |
| Power | 2800 W | |
| Welding rod | ø 4 mm / 0.16 in | |
| Material output ø 4 mm | 1.3-1.8 kg/h | 2.86-3.96 lb/h |
| Welding materials | HDPE; LDPE; LLDPE; PP | |
| Weldable sheet/membrane thickness | 10-15 mm | 0.39-0.59 in |
| Air guide | Internal | |
| Screw heating | Air heated | |
| Air temperature control | Open loop | |
| LQS | No | |
| Display | No | |
| Brushless blower motor | No | |
| Brushless drive motor | No | |
| LED Working light | No | |
| Length | 450 mm | 17.71 in |
| Width | 98 mm | 3.85 in |
| Height | 225 mm | 8.85 in |
| Weight | 5.9 kg | 13 lb |
| Power cable length | 5 m | 16.4 ft |
| Plug | CH T23, 3 poles, 16A | |
| Noise emission level | 86 dB (A) | |



FUSION 2

FUSION 2, 230V/2800W, CH plug

Article 176.837

Technical data

Approvals CB Certification; CE

Protection class II

Country of origin Switzerland

Scope of delivery

145.945 Welding shoe blank 45x30x54 IA; 119.540 Tool case