

TWINNY S

TWINNY S, 120V/1900W, combi-wedge short, 144:1, UK plug
Article 119.016



[To the product item](#)

Technical data

Article	119.016	
Voltage	120 V	
Frequency	50/60 Hz	
Power	1900 W	
Temperature	20-600 °C	68-1112 °F
Air volume adjustable	Yes	
Speed	0.8-4 m/min	2.62-13.12 ft/min
Welding Technology	Combi-wedge	
Combi-wedge version	Short	
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Roll material	Steel roller sharp diagonal	
LQS	No	
Brushless blower motor	No	
Display	No	
Length	350 mm	13.77 in
Width	390 mm	15.35 in
Height	270 mm	10.62 in
Weight	6.9 kg	15.21 lb
Welding materials	CSPE; EPDM; FPO; HDPE; LDPE; LLDPE; PP; PVC; TPO	
Weldable material thicknesses	0.3-2 mm	11.81-78.74 mil
Plug	UK, 3 poles, 13A	
Power cable length	3 m	9.84 ft



TWINNY S

TWINNY S, 120V/1900W, combi-wedge short, 144:1, UK plug
Article 119.016

Technical data

Approvals	CE
Protection class	II
Country of origin	Switzerland

Scope of delivery

126.448 Tool case