

# CHINOOK

CHINOOK, 3 x 230/400V 50Hz, 3 x 265/460V 60Hz

Article 177.073



**To the product item**

## Technical data

Blower type	Side channel blower	
Phases	3x	
Voltage at 50 Hz	230/400 V	
Voltage at 60 Hz	265/460 V	
Frequency	50/60 Hz	
Blower power at 50 Hz	750 W	
Blower power at 60 Hz	860 W	
Airflow (20 °C) at 50 Hz	1600 l/min	56.5 cfm
Airflow (20 °C) at 60 Hz	1900 l/min	67.09 cfm
Static pressure at 50 Hz	14500 Pa	2.1 psi
Static pressure at 60 Hz	15000 Pa	2.17 psi
Min. air inlet temperature	60 °C	140 °F
Max. air inlet temperature	350 °C	662 °F
Max. ambient temperature	60 °C	140 °F
Noise emission level	58 dB (A)	
Air inlet (outer diameter)	38 mm	1.49 in
Air outlet (outer diameter)	38 mm	1.49 in
Length	285 mm	11.22 in
Width	267 mm	10.51 in
Height	271 mm	10.66 in
Weight	14.85 kg	32.73 lb
Approvals	CE	
Protection class (IEC 60529)	IP55	
Protection class	I	