

TRIAC AT



关于产品



技术数据

订货号	141.314; 141.316; 141.317; 141.319; 141.320; 141.321; 141.322; 141.323; 142.737; 148.005	
电压	100 V; 120 V; 220 V; 230 V	
频率	50/60 Hz; 60 Hz	
功率	1500–1600 W	
温度	40–620 °C	104–1148 °F
无级温度调节	有	
风量 (20°C)	120–240 l/min	4.23–8.47 cfm
无级风量调节	有	
静风压	3000 Pa	0.43 psi
Eco-Mode	有	
显示	有	
e-Drive	有	
户外应用	有	
风嘴接口ø	31.5 mm / 1.25 in; M14	
长度	335 mm	13.18 in
设备直径	90 mm	3.54 in
手柄直径	56 mm	2.2 in
重量	1.02 kg	2.24 lb
电源线长度	3 m	9.84 ft

TRIAC AT

技术数据

插头	AU, 3极, 10A; CEE 黄色, 3 极, 16A; CH T11, 2极, 10A; CN, 2极, 10A; JP, 2极, 15A; KR, 2极, 16A; 欧盟, 2极, 16A; 美国, 2极, 15A, 极化处理; 英国, 3极, 13A
噪声等级	67 dB (A)
认证	CE; KC; S+; cULus
保护等级	II
批准号	MSIP-REM-Le1-TriacAT
原籍国	瑞士

交付范围

工具箱

订货号

141.314	TRIAC AT, 230V/1600W, 欧标插头
141.316	TRIAC AT, 120V/1600W, 美标插头
141.317	TRIAC AT, 100V/1500W, 日标插头
141.319	TRIAC AT, 120V/1600W, CEE 3/16
141.320	TRIAC AT, 230V/1600W, 英标插头
141.321	TRIAC AT, 230V/1600W, 澳标插头
141.322	TRIAC AT, 230V/1600W, 瑞标插头
141.323	TRIAC AT, 230V/1600W, 国标插头
142.737	TRIAC AT, 230V/1600W, 欧标插头, 螺纹风嘴
148.005	TRIAC AT, 220V/1600W, 韩标插头