

# LE 5000 HT-U / HT-S



**To the product**

## Technical data

Article	116.761; 116.763; 127.581; 127.582; 163.564; 163.565	
Phases	3x	
Voltage	200-480 V	
Current	9-20 A	
Power	7000-7500 W	
Max. air outlet temperature	900 °C	1652 °F
Min. airflow	400 l/min	14.12 cfm
Max. air inlet temperature	80 °C	176 °F
Max. ambient temperature	80 °C	176 °F
Overheating protection	No	
Max. inlet pressure	100 kPa	14.5 psi
Temperature sensor Type	K	
Version	Type S; Type U	
Length	224.5 mm	8.83 in
Width	234 mm	9.21 in
Height	326-327 mm	12.83-12.87 in
Weight	9 kg	19.84 lb
Power cable length	5 m	16.4 ft
Additional description	With insulation and thermocouple Typ K	
Approvals	CE; cURus	
Protection class	I	



# LE 5000 HT-U / HT-S

## Product items

---

116.761	LE 5000 HT-U, 3 x 400V/7.5kW
116.763	LE 5000 HT-S, 3 x 400V/7.5kW
127.581	LE 5000 HT-U, 3 x 480V/7.5kW
127.582	LE 5000 HT-S, 3 x 480V/7.5kW
163.564	LE 5000 HT-U, 3 x 200V/7.0kW
163.565	LE 5000 HT-S, 3 x 200V/7.0kW