

# LHS 61L CLASSIC



**To the product**

## Technical data

Phases	3x	
Current	7-25 A	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	390-1250 l/min	13.77-44.14 cfm
Max. air inlet temperature	65 °C	149 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	No	
Alarm output	Normally open contact	
Max. inlet pressure	100 kPa	14.5 psi
Nozzle connection ø	92 mm / 3.6 in	
Display	No	
Length	363.0 mm	14.29 in
Width	116.0 mm	4.56 in
Height	136.0 mm	5.35 in
Weight	3.65 kg	8.04 lb
Approvals	CE; S+; UKCA	
Protection class	I	



# LHS 61L CLASSIC

## Product items

---

143.487	LHS 61L CLASSIC, 3 x 480V/16kW
143.488	LHS 61L CLASSIC, 3 x 400V/16kW
143.489	LHS 61L CLASSIC, 3 x 230V/10kW
143.699	LHS 61L CLASSIC, 3 x 400V/11kW
143.700	LHS 61L CLASSIC, 3 x 480V/11kW
143.710	LHS 61L CLASSIC, 3 x 230V/8kW
143.711	LHS 61L CLASSIC, 3 x 400V/5kW
143.712	LHS 61L CLASSIC, 3 x 400V/8kW
143.713	LHS 61L CLASSIC, 3 x 480V/8kW