

DIODE S



To the product

Technical data

Article	101.279; 101.280; 101.281; 101.282; 101.283; 101.289; 101.291; 101.292; 135.971; 177.270	
Voltage	120 V; 200 V; 230 V	
Frequency	50/60 Hz	
Power	1400–2000 W	
Temperature	20–600 °C	68–1112 °F
Temperature setting stepless	Yes	
Air hose length	3 m	9.84 ft
Display	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	265 mm	10.43 in
Device diameter	57 mm	2.24 in
Handle diameter	40 mm	1.57 in
Weight	0.46 kg	1.01 lb
Plug	CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; US, 2 poles, 15A, polarized; without plug	
Approvals	CB Certification; CE	
Protection class	II	
Country of origin	Switzerland	



DIODE S

Product items

101.279	DIODE S, 230V/2000W, EU plug
101.280	DIODE S, 230V/2000W, M14, EU plug
101.281	DIODE S, 230V/1600W, EU plug
101.282	DIODE S, 230V/1600W, M14, EU plug
101.283	DIODE S, 230V/1600W, CH plug
101.289	DIODE S, 200V/1400W, w/o plug
101.291	DIODE S, 120V/1600W, US plug
101.292	DIODE S, 120V/1600W, M14, US plug
135.971	DIODE S, 230V/1600W, CN plug
177.270	DIODE S, 230V/1600W, M14, CN plug