

TWINNY T7



To the product



Technical data

Article	164.197; 164.198; 164.214; 164.215; 164.216; 164.217; 164.218; 164.219; 164.220	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3450 W	
Temperature	100-560 °C	212-1040 °F
Air volume adjustable	Yes	
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Combi-wedge	
Combi-wedge version	Long; Short	
Hot wedge width	50 mm	1.96 in
Hot wedge material	Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Silicone roller 70 shore A; Steel roller blunt diagonal; Steel roller sharp diagonal	
Travel roller equipment	Field-Kit; Indoor-Kit	
LQS	Yes	
Brushless blower motor	Yes	
Display	Yes	
Length	350 mm	13.77 in
Width	360 mm	14.17 in

TWINNY T7

Technical data

Height	260 mm	10.23 in
Weight	10.5 kg	23.14 lb
Welding materials	CSPE; EPDM; FPO; HDPE; LDPE; LLDPE; PP; PVC; TPO	
Weldable material thicknesses	0.3-3 mm	11.81-118.11 mil
Plug	CEE blue, 3 poles, 16A; EU, 3 poles, 16A	
Power cable length	3 m	9.84 ft
Approvals	CE	
Protection class	I	
Country of origin	Switzerland	

Scope of delivery

Cylinder brush, brass ø 15 mm; Test certificate; Tool case

Product items

164.197	TWINNY T7, 230V/3450W, combi-wedge long test channel, EU plug
164.198	TWINNY T7, 230V/3450W, combi-wedge long test channel, CEE 3/16
164.214	TWINNY T7, 230V/3450W, combi-wedge short test channel, EU plug
164.215	TWINNY T7, 230V/3450W, combi-wedge short test channel, CEE 3/16
164.216	TWINNY T7, 230V/3450W, combi-wedge long, EU plug
164.217	TWINNY T7, 230V/3450W, combi-wedge long, CEE 3/16
164.218	TWINNY T7, 230V/3450W, combi-wedge short, EU plug
164.219	TWINNY T7, 230V/3450W, combi-wedge short, CEE 3/16
164.220	TWINNY T7, 230V/3450W, combi-wedge short, silicone, EU plug