

COMET 500



To the product



Technical data

Article	170.562; 170.563; 170.565	
Voltage	230 V	
Frequency	50/60 Hz	
Power	2300 W	
Temperature	80-460 °C	176-860 °F
Speed	0.8-8 m/min	2.62-26.24 ft/min
Welding Technology	Hot wedge	
Hot wedge length	60 mm	2.36 in
Hot wedge width	50 mm	1.96 in
Hot wedge material	Copper; Stainless steel	
Max. overlap	125 mm	4.92 in
Max. welding pressure	1000 N	224.8 lbf
Weld seam width	2 x 15 mm / 2 x 0.59 in	
Roll material	Steel roller blunt diagonal; Steel roller sharp diagonal	
Travel roller equipment	Field-Kit; Indoor-Kit	
LQS	No	
Display	Yes	
Length	325 mm	12.79 in
Width	245 mm	9.64 in
Height	260 mm	10.23 in
Weight	9.2 kg	20.28 lb



COMET 500

Technical data

Welding materials	CSPE; FPO; HDPE; LDPE; LLDPE; PE; PP; PVC; TPO	
Weldable material thicknesses	0.5-3 mm	19.68-118.11 mil
Power cable length	3 m	9.84 ft
Plug	CEE blue, 3 poles, 16A	
Approvals	CE	
Protection class	I	
Country of origin	Switzerland	

Scope of delivery

Cylinder brush, brass ø 15 mm; Tool case

Product items

170.562	COMET 500, 230V/2300W, copper 60x50mm test channel, CEE 3/16
170.563	COMET 500, 230V/2300W, steel 60x50mm test channel, CEE 3/16
170.565	COMET 500, 230V/2300W, steel 60x50mm, CEE 3/16