

# WELDPLAST S2



**To the product**

## Technical data

Article	127.215; 140.707; 146.341; 156.131; 176.839	
Voltage	200 V; 230 V	
Frequency	50/60 Hz	
Power	2400-3000 W	
Welding rod	ø 3-4 mm / 0.12-0.16 in	
Material output ø 3 mm	0.6-1.3 kg/h	1.32-2.86 lb/h
Material output ø 4 mm	1-2 kg/h	2.2-4.4 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Weldable sheet/membrane thickness	10-20 mm	0.39-0.78 in
Air guide	Internal	
Screw heating	Coil heater	
Air temperature control	Closed loop	
LQS	No	
Display	Yes	
Brushless blower motor	Yes	
Brushless drive motor	No	
LED Working light	No	
Length	450 mm	17.71 in
Width	98 mm	3.85 in
Height	260 mm	10.23 in
Weight	5.8 kg	12.78 lb



# WELDPLAST S2

## Technical data

Power cable length	3-5 m	9.84-16.4 ft
Plug	CEE blue, 3 poles, 16A; CH T23, 3 poles, 16A; CN, 3 poles, 16A; EU, 3 poles, 16A; without plug	
Noise emission level	78 dB (A)	
Approvals	CE; KC	
Protection class	I	
Country of origin	Switzerland	

## Scope of delivery

Welding Shoe; Tool case

## Product items

127.215	WELDPLAST S2, 230V/3000W, EU plug
140.707	WELDPLAST S2, 230V/3000W, CN plug
146.341	WELDPLAST S2, 200V/2400W, w/o plug
156.131	WELDPLAST S2, 230V/3000W, CEE 3/16
176.839	WELDPLAST S2, 230V/3000W, CH plug