

# TWINNY S



**To the product**



## Technical data

|                        |                                                      |                   |
|------------------------|------------------------------------------------------|-------------------|
| Article                | 119.016; 119.024; 119.031; 119.039; 128.778; 179.384 |                   |
| Voltage                | 120-230 V                                            |                   |
| Frequency              | 50/60 Hz                                             |                   |
| Power                  | 1900-2900 W                                          |                   |
| Temperature            | 20-600 °C                                            | 68-1112 °F        |
| Air volume adjustable  | Yes                                                  |                   |
| Speed                  | 0.2-4 m/min                                          | 0.65-13.12 ft/min |
| Welding Technology     | Combi-wedge                                          |                   |
| Combi-wedge version    | Long; Short                                          |                   |
| Hot wedge width        | 50 mm                                                | 1.96 in           |
| Hot wedge material     | Stainless steel                                      |                   |
| Max. overlap           | 125 mm                                               | 4.92 in           |
| Max. welding pressure  | 1000 N                                               | 224.8 lbf         |
| Weld seam width        | 2 x 15 mm / 2 x 0.59 in                              |                   |
| Roll material          | Steel roller sharp diagonal                          |                   |
| LQS                    | No                                                   |                   |
| Brushless blower motor | No                                                   |                   |
| Display                | No                                                   |                   |
| Length                 | 350 mm                                               | 13.77 in          |
| Width                  | 390 mm                                               | 15.35 in          |
| Height                 | 270 mm                                               | 10.62 in          |



# TWINNY S

## Technical data

|                               |                                                                          |                  |
|-------------------------------|--------------------------------------------------------------------------|------------------|
| Weight                        | 6.9 kg                                                                   | 15.21 lb         |
| Welding materials             | CSPE; EPDM; FPO; HDPE; LDPE; LLDPE; PP; PVC; TPO                         |                  |
| Weldable material thicknesses | 0.3-3 mm                                                                 | 11.81-118.11 mil |
| Plug                          | CEE blue, 3 poles, 16A; EU, 3 poles, 16A; UK, 3 poles, 13A; without plug |                  |
| Power cable length            | 3 m                                                                      | 9.84 ft          |
| Approvals                     | CE; KC                                                                   |                  |
| Protection class              | II                                                                       |                  |
| Country of origin             | Switzerland                                                              |                  |

## Scope of delivery

Tool case

## Product items

|         |                                                          |
|---------|----------------------------------------------------------|
| 119.016 | TWINNY S, 120V/1900W, combi-wedge short, 144:1, UK plug  |
| 119.024 | TWINNY S, 230V/2900W, combi-wedge short, 144:1, EU plug  |
| 119.031 | TWINNY S, 230V/2900W, combi-wedge long, 256:1, EU plug   |
| 119.039 | TWINNY S, 120V/1900W, combi-wedge long, 256:1, w/o plug  |
| 128.778 | TWINNY S, 230V/2900W, combi-wedge long, 256:1, CEE 3/16  |
| 179.384 | TWINNY S, 230V/2900W, combi-wedge short, 144:1, CEE 3/16 |