

DIODE S with MINOR



To the product



Technical data

Article	101.441; 101.447; 101.449; 136.241	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1500-1700 W	
Temperature	20-600 °C	68-1112 °F
Temperature setting stepless	Yes	
Stepless air volume adjustment	No	
Static pressure	5000 Pa	0.72 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	256 mm	10.07 in
Device diameter	57 mm	2.24 in
Handle diameter	40 mm	1.57 in
Power cable length	3 m	9.84 ft
Air hose length	1.5 m	4.92 ft
Plug	CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	



DIODE S with MINOR

Technical data

Approvals	CB Certification; CE
Protection class	II
Country of origin	Switzerland

Product items

101.441	DIODE S/MINOR, 230V/1700W, EU plug
101.447	DIODE S/MINOR, 120V/1700W, US plug
101.449	DIODE S/MINOR, 100V/1500W, JP plug
136.241	DIODE S/MINOR, 230V/1700W, CN plug