

energy HT1600



To the product



Technical data

Article	120.881; 123.898; 126.732; 127.007; 148.003	
Voltage	120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	1600 W	
Temperature	40-700 °C	104-1292 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	346 mm	13.62 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	0.99 kg	2.18 lb
Power cable length	3 m	9.84 ft
Plug	CN, 2 poles, 10A; EU, 2 poles, 16A; KR, 2 poles, 16A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized	

energy HT1600

Technical data

Noise emission level	67 dB (A)
Approvals	CE; KC
Protection class	II
Approval number	R-R-Le5-energyHT1600
Country of origin	P.R. China

Product items

120.881	energy HT1600, 230V/1600W, EU plug
123.898	energy HT1600, 120V/1600W, US plug
126.732	energy HT1600, 230V/1600W, UK plug
127.007	energy HT1600, 220V/1600W, KR plug
148.003	energy HT1600, 230V/1600W, CN plug