

energy HT1600 D



To the product



Technical data

Article	160.170; 160.173; 160.176; 160.179	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1600 W	
Temperature	40-620 °C	104-1148 °F
Temperature setting stepless	Yes	
Airflow (20°C)	120-240 l/min	4.23-8.47 cfm
Stepless air volume adjustment	Yes	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	360 mm	14.17 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	1.2 kg	2.64 lb
Power cable length	3 m	9.84 ft
Plug	CN, 2 poles, 10A; EU, 2 poles, 16A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	

energy HT1600 D

Technical data

Approvals	CE
Protection class	II
Country of origin	P.R. China

Product items

160.170	energy HT1600 D, 230V/1600W, EU plug
160.173	energy HT1600 D, 230V/1600W, UK plug
160.176	energy HT1600 D, 230V/1600W, CN plug
160.179	energy HT1600 D, 120V/1600W, US plug