

FUSION 2



To the product



Technical data

Article	119.200; 139.197; 150.102; 166.366; 176.837; 179.193	
Voltage	120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	2600-2800 W	
Welding rod	ø 4 mm / 0.16 in	
Material output ø 4 mm	1.3-1.8 kg/h	2.86-3.96 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Weldable sheet/membrane thickness	10-15 mm	0.39-0.59 in
Air guide	Internal	
Screw heating	Air heated	
Air temperature control	Open loop	
LQS	No	
Display	No	
Brushless blower motor	No	
Brushless drive motor	No	
LED Working light	No	
Length	450 mm	17.71 in
Width	98 mm	3.85 in
Height	225 mm	8.85 in
Weight	5.9 kg	13 lb
Power cable length	3-5 m	9.84-16.4 ft

FUSION 2

Technical data

Plug	CEE blue, 3 poles, 16A; CEE yellow, 3 poles, 16A; CH T23, 3 poles, 16A; EU, 2 poles, 16A; KR, 2 poles, 16A; without plug
Noise emission level	86 dB (A)
Approvals	CB Certification; CE; KC; UKCA
Protection class	II
Country of origin	Switzerland

Scope of delivery

Welding shoe blank 45x30x54 IA; Tool case

Product items

119.200	FUSION 2, 230V/2800W, EU plug
139.197	FUSION 2, 230V/2800W, CEE 3/16
150.102	FUSION 2, 120V/2800W, CEE 3/16
166.366	FUSION 2, 220V/2600W, KR plug
176.837	FUSION 2, 230V/2800W, CH plug
179.193	FUSION 2, 230V/2800W, w/o shoe, w/o plug