

FUSION 3C



To the product

Technical data

Voltage	220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	3000-3200 W	
Welding additive	ø 3-4 mm / 0.12-0.16 in; ø 4-5 mm / 0.16-0.2 in	
Max. material output	3.6 kg/h	7.93 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Air guide	Internal	
Screw heating	Air heated	
Air temperature control	Open loop	
LQS	No	
Display	No	
Brushless blower motor	No	
Brushless drive motor	No	
LED Working light	No	
Length	588.0 mm	23.14 in
Width	98.0 mm	3.85 in
Height	225.0 mm	8.85 in
Weight	6.9 kg	15.21 lb
Power cable length	3.0-5.0 m	9.84-16.4 ft
Noise emission level	86 dB (A)	



FUSION 3C

Technical data

Approvals	CB Certification; CE; KC; UKCA
Protection class	II
Country of origin	CH

Scope of delivery

Welding shoe blank 45x30x54 IA; Tool case

Product items

123.866	FUSION 3C, 230V/3200W, ø3/4mm, EU plug
140.028	FUSION 3C, 230V/3200W, ø3/4mm, CEE 3/16
143.837	FUSION 3C, 230V/3200W, ø4/5mm, CEE 3/16
144.826	FUSION 3C, 230V/3200W, ø4/5mm, EU plug
166.365	FUSION 3C, 220V/3000W, ø3/4mm, KR plug
173.794	FUSION 3C, 230V/3200W, ø3/4mm, w/o shoe, CEE 3/16
176.838	FUSION 3C, 230V/3200W, ø3/4mm, CH plug