

# GHIBLI AW



**To the product**

## Technical data

Article	148.061; 148.078; 148.079; 150.168; 150.169; 150.170	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1500-2300 W	
Temperature	65-620 °C	149-1148 °F
Temperature setting stepless	Yes	
Airflow (20°C)	140-250 l/min	4.94-8.82 cfm
Stepless air volume adjustment	Yes	
Static pressure	3200 Pa	0.46 psi
Eco-Mode	No	
Display	Yes	
e-Drive	Yes	
Outdoor use	Yes	
Nozzle connection ø	36.5 mm / 1.45 in	
Length	280 mm	11.02 in
Width	90 mm	3.54 in
Height	220 mm	8.66 in
Handle diameter	45 mm	1.77 in
Weight	1.18 kg	2.6 lb
Power cable length	3 m	9.84 ft



# GHIBLI AW

## Technical data

Plug	CEE yellow, 3 poles, 16A; CH T11, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized
Noise emission level	67 dB (A)
Approvals	CE
Protection class	II
Country of origin	Switzerland

## Scope of delivery

Stand; Tool case

## Product items

148.061	GHIBLI AW, 230V/2300W, EU plug
148.078	GHIBLI AW, 120V/1800W, US plug
148.079	GHIBLI AW, 100V/1500W, JP plug
150.168	GHIBLI AW, 230V/2300W, UK plug
150.169	GHIBLI AW, 230V/2300W, CH plug
150.170	GHIBLI AW, 120V/1800W, CEE 3/16