

HEMTEK ST



关于产品



技术数据

订货号	157.860; 157.861; 157.862; 157.866; 157.867; 157.868; 157.869; 157.870; 157.871	
电压	120 V; 230 V	
频率	50/60 Hz	
功率	1800–3450 W	
速度	0.8–12 m/min	2.62–39.37 ft/min
温度	100–650 °C	212–1202 °F
风量可调	有	
风嘴/焊缝宽度	20–40 mm	0.78–1.57 in
长度	433 mm	17.04 in
宽度	350 mm	13.77 in
高度	600 mm	23.62 in
重量	27 kg	59.52 lb
插头	CEE蓝色, 3极, 16A.; 欧盟, 3极, 16A; 美国, 3极, 15A	
电源线长度	3 m	9.84 ft
认证	CB认证; CE	
保护等级	I	
原籍国	瑞士	

交付范围

可调节的折边穿绳导向件; 橡胶塞子

HEMTEK ST

订货号

157.860	HEMTEK ST, 230V/3450W, 40mm, 欧标插头
157.861	HEMTEK ST, 230V/3450W, 30mm, 欧标插头
157.862	HEMTEK ST, 230V/2350W, 20mm, 欧标插头
157.866	HEMTEK ST, 230V/3450W, 40mm, CEE 3/16
157.867	HEMTEK ST, 230V/3450W, 30mm, CEE 3/16
157.868	HEMTEK ST, 230V/2350W, 20mm, CEE 3/16
157.869	HEMTEK ST, 120V/1800W, 40mm, 美标插头
157.870	HEMTEK ST, 120V/1800W, 30mm, 美标插头
157.871	HEMTEK ST, 120V/1800W, 20mm, 美标插头