

HEMTEK ST



Over het product



Technische gegevens

Artikel	157.860; 157.861; 157.862; 157.866; 157.867; 157.868; 157.869; 157.870; 157.871	
Spanning	120 V; 230 V	
Frequentie	50/60 Hz	
Vermogen	1800-3450 W	
Snelheid	0.8-12 m/min	2.62-39.37 ft/min
Temperatuur	100-650 °C	212-1202 °F
Luchthoeveelheid instelbaar	Ja	
Lasmondstuk / naadbreedte	20-40 mm	0.78-1.57 in
Lengte	433 mm	17.04 in
Breedte	350 mm	13.77 in
Hoogte	600 mm	23.62 in
Gewicht	27 kg	59.52 lb
Stekker	CEE blauw, 3-polig, 16A; EU, 3-polig, 16A; US, 3-polig, 15A	
Lengte voedingskabel	3 m	9.84 ft
Goedkeuringen	CB Certificering; CE	
Beschermingsklasse	I	
Land van herkomst	Zwitserland	

Omvang van de levering

Verstelbare zoom en keder geleider; Rubberen stop

HEMTEK ST

Artikel

157.860	HEMTEK ST, 230V/3450W, 40mm, EU stekker
157.861	HEMTEK ST, 230V/3450W, 30mm, EU stekker
157.862	HEMTEK ST, 230V/2350W, 20mm, EU stekker
157.866	HEMTEK ST, 230V/3450W, 40mm, CEE 3/16
157.867	HEMTEK ST, 230V/3450W, 30mm, CEE 3/16
157.868	HEMTEK ST, 230V/2350W, 20mm, CEE 3/16
157.869	HEMTEK ST, 120V/1800W, 40mm, VS stekker
157.870	HEMTEK ST, 120V/1800W, 30mm, VS stekker
157.871	HEMTEK ST, 120V/1800W, 20mm, VS stekker