

HEMTEK ST



Acerca del producto



Datos técnicos

Artículo	157.860; 157.861; 157.862; 157.866; 157.867; 157.868; 157.869; 157.870; 157.871	
Voltaje	120 V; 230 V	
Frecuencia	50/60 Hz	
Potencia	1800-3450 W	
Velocidad	0.8-12 m/min	2.62-39.37 ft/min
Temperatura	100-650 °C	212-1202 °F
Volumen de aire ajustable	Sí	
Boquilla de soldadura / ancho de costura	20-40 mm	0.78-1.57 in
Longitud	433 mm	17.04 in
Ancho	350 mm	13.77 in
Altura	600 mm	23.62 in
Peso	27 kg	59.52 lb
Enchufe	CEE azul, 3 polos, 16A; UE, 3 polos, 16A; US, 3 polos, 15A	
La longitud del cable de alimentación	3 m	9.84 ft
Aprobaciones	CE; Certificación CB	
Clase de protección	I	
País de origen	Suiza	

Alcance de la entrega

Dobladillo ajustable y guía de tubería; Tapón de goma



HEMTEK ST

Artículos

157.860	HEMTEK ST, 230V/3450W, 40mm, enchufe UE
157.861	HEMTEK ST, 230V/3450W, 30mm, enchufe UE
157.862	HEMTEK ST, 230V/2350W, 20mm, enchufe UE
157.866	HEMTEK ST, 230V/3450W, 40mm, CEE 3/16
157.867	HEMTEK ST, 230V/3450W, 30mm, CEE 3/16
157.868	HEMTEK ST, 230V/2350W, 20mm, CEE 3/16
157.869	HEMTEK ST, 120V/1800W, 40mm, enchufe EE.UU.
157.870	HEMTEK ST, 120V/1800W, 30mm, enchufe EE.UU.
157.871	HEMTEK ST, 120V/1800W, 20mm, enchufe EE.UU.