

HG 330-B Universal Kit



To the product



Technical data

Article	120.128; 123.155; 124.403; 131.321; 133.771; 134.690; 164.323	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1100-1600 W	
Temperature	350-550 °C	662-1022 °F
Temperature at level 1	350 °C	662 °F
Temperature at level 2	550 °C	1022 °F
Temperature setting stepless	No	
Air volume at level 1	250-350 l/min	8.82-12.36 cfm
Air volume at level 2	400-500 l/min	14.12-17.65 cfm
Stepless air volume adjustment	No	
Eco-Mode	No	
Display	No	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	250 mm	9.84 in
Width	80 mm	3.14 in
Height	230 mm	9.05 in
Handle diameter	45 mm	1.77 in
Weight	0.7 kg	1.54 lb
Power cable length	2 m	6.56 ft

HG 330-B Universal Kit

Technical data

Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 12A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized
Noise emission level	67 dB (A)
Approvals	CE; cULus
Protection class	II
Country of origin	P.R. China

Scope of delivery

Glass protection nozzle (ø 35.5) 50 x 5 mm; Spoon reflector (ø 35.5) 40 x 35 mm

Product items

120.128	HG 330-B, 100V/1100W, Universal Kit, JP plug
123.155	HG 330-B, 120V/1200W, Universal Kit, US plug
124.403	HG 330-B, 230V/1600W, Universal Kit, CN plug
131.321	HG 330-B, 230V/1600W, Universal Kit, UK plug
133.771	HG 330-B, 230V/1600W, Universal Kit, AU plug
134.690	HG 330-B, 230V/1600W, Universal Kit, CH plug
164.323	HG 330-B, 230V/1600W, Universal Kit, EU plug