

HG 530-A Universal Kit



To the product



Technical data

Article	120.132; 123.159; 124.407; 131.325; 133.775; 134.694; 164.327	
Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1300-2300 W	
Temperature	80-650 °C	176-1202 °F
Temperature setting stepless	Yes	
Airflow (20°C)	200-550 l/min	7.06-19.42 cfm
Stepless air volume adjustment	Yes	
Eco-Mode	Yes	
Display	Yes	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	250 mm	9.84 in
Width	80 mm	3.14 in
Height	230 mm	9.05 in
Handle diameter	45 mm	1.77 in
Weight	0.75 kg	1.65 lb
Power cable length	2 m	6.56 ft
Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 15A; UK, 3 poles, 13A; US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	

HG 530-A Universal Kit

Technical data

Approvals	CE; cULus
Protection class	II
Country of origin	P.R. China

Scope of delivery

Spoon reflector (ø 35.5) 40 x 35 mm; Tubular nozzle (ø 35.5) ø 6 mm, 75 mm; Wide slot nozzle (ø 35.5) 25 x 3 mm; Solder reflector (ø 35.5) 13 x 5 x 10 mm; Pressure roller 30 mm, ABS

Product items

120.132	HG 530-A, 100V/1300W, Universal Kit, JP plug
123.159	HG 530-A, 120V/1440W, Universal Kit, US plug
124.407	HG 530-A, 230V/2300W, Universal Kit, CN plug
131.325	HG 530-A, 230V/2300W, Universal Kit, UK plug
133.775	HG 530-A, 230V/2300W, Universal Kit, AU plug
134.694	HG 530-A, 230V/2300W, Universal Kit, CH plug
164.327	HG 530-A, 230V/2300W, Universal Kit, EU plug