

# HOT JET S



To the product



## Technical data

Article	100.648; 100.688; 100.854; 100.859; 100.862; 100.863; 138.414; 140.030	
Voltage	100 V; 120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	460 W	
Temperature	20-600 °C	68-1112 °F
Temperature setting stepless	Yes	
Airflow (20°C)	20-80 l/min	0.7-2.82 cfm
Stepless air volume adjustment	Yes	
Static pressure	1600 Pa	0.23 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	21.3 mm / 0.85 in	
Length	235 mm	9.25 in
Device diameter	70 mm	2.75 in
Handle diameter	40 mm	1.57 in
Weight	0.36 kg	0.79 lb
Power cable length	3 m	9.84 ft
Plug	AU, 3 poles, 10A; CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; JP, 2 poles, 12A; KR, 2 poles, 16A; US, 2 poles, 15A, polarized; without plug	



# HOT JET S

## Technical data

Noise emission level	56 dB (A)
Approvals	CE; KC; S+; UL
Protection class	II
Approval number	MSIP-REM-Le1-Hot-JetS
Country of origin	Switzerland

## Product items

100.648	HOT-JET S, 230V/460W, EU plug
100.688	HOT-JET S, 230V/460W, CH plug
100.854	HOT-JET S, 230V/460W, AU plug
100.859	HOT-JET S, 120V/460W, US plug
100.862	HOT-JET S, 120V/460W, w/o plug
100.863	HOT-JET S, 100V/460W, JP plug
138.414	HOT-JET S, 230V/460W, CN plug
140.030	HOT-JET S, 220V/460W, KR plug