

HT 330-S Universal Kit



To the product

Technical data

Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1200-2000 W	
Temperature	80-600 °C	176.0-1112.0 °F
Temperature setting stepless	Yes	
Air volume at level 1	250 l/min	8.82 cfm
Air volume at level 2	450-550 l/min	15.89-19.42 cfm
Stepless air volume adjustment	No	
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	359.0 mm	14.13 in
Device diameter	90 mm	3.54 in
Handle diameter	50 mm	1.96 in
Weight	0.65 kg	1.43 lb
Power cable length	2.0 m	6.56 ft
Noise emission level	67 dB (A)	

HT 330-S Universal Kit

Technical data

Approvals	CE
Protection class	II
Country of origin	CN

Scope of delivery

Glass protection nozzle (ø 35.5) 50 x 5 mm; Tubular nozzle (ø 35.5) ø 20 mm, 30 mm; Spoon reflector (ø 35.5) 40 x 35 mm

Product items

128.727	HT 330-S, 100V/1200W, Universal Kit, JP plug
128.770	HT 330-S, 120V/1400W, Universal Kit, US plug
128.779	HT 330-S, 230V/2000W, Universal Kit, AU plug
128.780	HT 330-S, 230V/2000W, Universal Kit, CN plug
128.781	HT 330-S, 230V/2000W, Universal Kit, EU plug
128.782	HT 330-S, 230V/2000W, Universal Kit, UK plug
129.824	HT 330-S, 230V/2000W, Universal Kit, CH plug