

HT 530-A Universal Kit



To the product



Technical data

Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1300-2300 W	
Temperature	80-650 °C	176.0-1202.0 °F
Temperature setting stepless	Yes	
Airflow (20°C)	200-550 l/min	7.06-19.42 cfm
Stepless air volume adjustment	Yes	
Eco-Mode	Yes	
Display	Yes	
e-Drive	Yes	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	359.0 mm	14.13 in
Device diameter	90 mm	3.54 in
Handle diameter	50 mm	1.96 in
Weight	0.7 kg	1.54 lb
Power cable length	2.0 m	6.56 ft
Noise emission level	67 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	CN	

HT 530-A Universal Kit

Scope of delivery

Spoon reflector (ø 35.5) 40 x 35 mm; Tubular nozzle (ø 35.5) ø 6 mm, 75 mm; Solder reflector (ø 35.5) 13 x 5 x 10 mm; Pressure roller 30 mm, ABS; Wide slot nozzle (ø 35.5) 25 x 3 mm

Product items

129.473	HT 530-A, 100V/1300W, Universal Kit, JP plug
129.475	HT 530-A, 120V/1500W, Universal Kit, US plug
129.550	HT 530-A, 230V/2300W, Universal Kit, AU plug
129.551	HT 530-A, 230V/2300W, Universal Kit, CN plug
129.552	HT 530-A, 230V/2300W, Universal Kit, EU plug
129.553	HT 530-A, 230V/2300W, Universal Kit, UK plug
129.894	HT 530-A, 230V/2300W, Universal Kit, CH plug