

# IGNITER BM4



关于产品



## 技术数据

|           |                                  |               |
|-----------|----------------------------------|---------------|
| 相位        | 1x                               |               |
| 电压        | 120–230 V                        |               |
| 功率        | 600–1600 W                       |               |
| 频率        | 50/60 Hz                         |               |
| 最高出风温度    | 500–600 °C                       | 932–1112 °F   |
| 风量 (20°C) | 80–230 l/min                     | 2.82–8.12 cfm |
| 最高进气温度    | 65 °C                            | 149 °F        |
| 最高环境温度    | 65 °C                            | 149 °F        |
| 过热保护      | 有                                |               |
| 静风压       | 300–2480 Pa                      | 0.04–0.35 psi |
| 风嘴接口ø     | 31.5 mm / 1.25 in; G 3/8 in; M14 |               |
| 噪声等级      | 58; 68 dB (A)                    |               |
| 显示        | 无                                |               |
| 长度        | 283 mm                           | 11.14 in      |
| 设备直径      | 90 mm                            | 3.54 in       |
| 重量        | 1 kg                             | 2.2 lb        |
| 认证        | CE; S+; cURus                    |               |
| 保护等级      | II                               |               |



# IGNITER BM4

## 订货号

---

|         |                               |
|---------|-------------------------------|
| 139.231 | IGNITER BM4, 230V/1600W       |
| 139.232 | IGNITER BM4, 230V/600W        |
| 140.711 | IGNITER BM4, 230V/1100W       |
| 141.881 | IGNITER BM4, 120V/1550W       |
| 142.421 | IGNITER BM4, 230V/1100W, 3/8" |
| 144.012 | IGNITER BM4, 230V/1100W, M14  |
| 145.449 | IGNITER BM4, 230V/1600W, M14  |