

IGNITER BM4



To the product



Technical data

Phases	1x	
Voltage	120-230 V	
Power	600-1600 W	
Frequency	50/60 Hz	
Max. air outlet temperature	500-600 °C	932-1112 °F
Airflow (20°C)	80-230 l/min	2.82-8.12 cfm
Max. air inlet temperature	65 °C	149 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	Yes	
Static pressure	300-2480 Pa	0.04-0.35 psi
Nozzle connection ø	31.5 mm / 1.25 in; G 3/8 in; M14	
Noise emission level	58; 68 dB (A)	
Display	No	
Length	283 mm	11.14 in
Device diameter	90 mm	3.54 in
Weight	1 kg	2.2 lb
Approvals	CE; S+; cURus	
Protection class	II	



IGNITER BM4

Product items

139.231	IGNITER BM4, 230V/1600W
139.232	IGNITER BM4, 230V/600W
140.711	IGNITER BM4, 230V/1100W
141.881	IGNITER BM4, 120V/1550W
142.421	IGNITER BM4, 230V/1100W, 3/8"
144.012	IGNITER BM4, 230V/1100W, M14
145.449	IGNITER BM4, 230V/1600W, M14