

LABOR S with MINOR



To the product

Technical data

Article	101.748; 101.749; 101.754; 101.755; 179.872	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	700-900 W	
Temperature	20-600 °C	68-1112 °F
Temperature setting stepless	Yes	
Stepless air volume adjustment	No	
Static pressure	5000 Pa	0.72 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	21.3 mm / 0.85 in	
Length	180 mm	7.08 in
Device diameter	40 mm	1.57 in
Handle diameter	32 mm	1.25 in
Power cable length	3 m	9.84 ft
Air hose length	1.5-3 m	4.92-9.84 ft
Plug	CH T11, 2 poles, 10A; CN, 2 poles, 10A; EU, 2 poles, 16A; US, 2 poles, 15A, polarized	
Noise emission level	67 dB (A)	



LABOR S with MINOR

Technical data

Approvals	CE
Protection class	II
Country of origin	Switzerland

Product items

101.748	LABOR S/MINOR, 230V/900W, 3m, EU plug
101.749	LABOR S/MINOR, 230V/900W, 3m, CH plug
101.754	LABOR S/MINOR, 230V/900W, EU plug
101.755	LABOR S/MINOR, 120V/700W, US plug
179.872	LABOR S/MINOR, 230V/900W, 3m, CN plug