

LE 10000 DF



To the product

Technical data

Article	114.555; 115.571; 116.135; 117.276; 117.759; 130.865	
Phases	3x	
Current	8-25 A	
Voltage	400-480 V	
Power	5500-17000 W	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	420-1300 l/min	14.83-45.9 cfm
Max. air inlet temperature	150 °C	302 °F
Max. ambient temperature	100 °C	212 °F
Overheating protection	No	
Max. inlet pressure	100 kPa	14.5 psi
Display	No	
Additionally sealed	No; Yes	
Length	167 mm	6.57 in
Device diameter	146 mm	5.74 in
Weight	3.4-4.5 kg	7.49-9.92 lb
Power cable length	5 m	16.4 ft
Approvals	CE; EAC; UKCA; cURus	
Protection class	I	



LE 10000 DF

Product items

114.555	LE 10000 DF, 3 x 400V/11kW
115.571	LE 10000 DF, 3 x 400V/5.5kW
116.135	LE 10000 DF, 3 x 400V/17kW
117.276	LE 10000 DF, 3 x 480V/8kW
117.759	LE 10000 DF, 3 x 480V/16kW
130.865	LE 10000 DF, 3 x 400V/17kW, sealed