

LE 10000 DF-C



To the product



Technical data

Article	146.288; 146.916; 147.323; 147.324; 147.325; 153.783; 154.088; 154.276	
Phases	3x	
Current	6-25 A	
Voltage	230-480 V	
Power	4500-17000 W	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	320-1300 l/min	11.3-45.9 cfm
Max. air inlet temperature	150 °C	302 °F
Max. ambient temperature	100 °C	212 °F
Overheating protection	No	
Max. inlet pressure	100 kPa	14.5 psi
Display	No	
Length	166.5 mm	6.55 in
Device diameter	146 mm	5.74 in
Weight	3.9-5.02 kg	8.59-11.06 lb
Power cable length	6 m	19.68 ft
Approvals	CE; UKCA; cURus	
Protection class	I	



LE 10000 DF-C

Product items

146.288	LE 10000 DF-C, 3 x 230V/8kW
146.916	LE 10000 DF-C, 3 x 230V/10kW
147.323	LE 10000 DF-C, 3 x 400V/5.5kW
147.324	LE 10000 DF-C, 3 x 400V/11kW
147.325	LE 10000 DF-C, 3 x 400V/17kW
153.783	LE 10000 DF-C, 3 x 480V/4.5kW
154.088	LE 10000 DF-C, 3 x 480V/8kW
154.276	LE 10000 DF-C, 3 x 480V/10kW