

LHS 410 SF



To the product



Technical data

Article	170.902; 170.903; 170.904; 170.905; 170.906; 170.907; 170.908	
Phases	1x	
Voltage	120-400 V	
Current	5-19.5 A	
Power	2000-5500 W	
Max. air outlet temperature	650 °C	1202 °F
Min. airflow	160-420 l/min	5.65-14.83 cfm
Max. air inlet temperature	100 °C	212 °F
Max. ambient temperature	65 °C	149 °F
Overheating protection	No	
Max. inlet pressure	100 kPa	14.5 psi
Nozzle connection ø	50 mm / 2 in	
Display	No	
Length	178 mm	7 in
Width	81 mm	3.18 in
Height	186 mm	7.32 in
Weight	1.55 kg	3.41 lb
Approvals	CE; S+; cURus	
Protection class	I	



LHS 410 SF

Product items

170.902	LHS 410 SF, 120V/2kW
170.903	LHS 410 SF, 230V/2kW
170.904	LHS 410 SF, 230V/3.6kW
170.905	LHS 410 SF, 230V/4.4kW
170.906	LHS 410 SF, 400V/2kW
170.907	LHS 410 SF, 400V/4.4kW
170.908	LHS 410 SF, 400V/5.5kW